



## Procedure for Replacement of Timer Bezel



Within the timer bezel replacement kit you will find the following items: a plastic cover profile (with your sunbed's logo and warning statements), 2 colored trim profiles and the new timer bezel. The cover profile and trim profiles are provided because the old style bezel is held in place with screws which go through the cover profile and trim profiles. The new ones will eliminate the holes left by the screws. Disconnect power before performing this procedure.

Refer to detail 1. To begin, pull off the timer knob (A). Remove all four silver screws (B) and the two bronze screws (C) holding the timer bezel (D) and wrap-around bezel piece (E) in place (see NOTE). Remove the colored trim profiles from the front of the canopy, the one on the acrylic side as well as the top side. Remove the cover profile by prying it from the aluminum side frame, at the center, and working out to the ends.

Now refer to detail 2. The new timer bezel (F) is held in place by the two bronze screws (C) and the colored trim profile. This improved design eliminates the need to remove the wrap-around bezel piece when the acrylic is removed. Snap the new cover profile in place. Start at the ends and work toward the center as the ends of the cover slide under the endcap. Put the new bezel (F) in place and secure with the bronze screws (C). Snap the trim profiles back in place to secure the canopy cover, timer bezel and acrylic. Again work from the ends to the center. Now press the timer knob (A) back on and the sunbed is ready to use.

**NOTE:** For units with face tanners you will have to remove the face tanner switch from the timer bezel. Unplug the wires leading to the switch, squeeze the sides of the switch and push out of the bezel. Install the switch in the new bezel, in the same orientation as it was removed, and reattach the wires.

